







MN16S Small Pixel LED DISPLAY

MN16S



Features

MN16S P1.667 Full Color Pixel Pitch Stage LED Display Screen

-  Cabinet weight is only 9.3 kg, depth 73 mm, decreasing the transportation cost and the intensity of labor.
-  Super thin power supply inside; Quiet fan design, excellent heat dissipation, noiseless.
-  Refresh rate > 1500HZ, 2 times higher than the regular screen, suitable for the rental occasion which requires much more higher display capability.
-  Super-light aluminium alloy connectors are durable and artistic.
-  Signal & power aviation connectors are water & dust proof, stable and reliable.
-  Cushion under the cabinet can protect the modules from being damaged.

Specification

Item	Value
Pixel Pitch(mm)	1.667mm
Pixel Density(pixels / m ²)	390,625dots/m ²
LED Configuration	1R,1G,1B
Colors	>16.7M
Brightness(nits)	800CD/M ²
Grey Level(bit)	14bit
Refresh Rate(Hz)	>1500HZ
Viewing Angle(Deg.)	H: 140/ V:140
Dimension(inch)	240mm x 240mm x 73mm
Resolution(pixels)	300 x 300mm
Panel Weight(kg)	9.3KG
Protection Level	IP43
Input Voltage	AC 110V~220V+/-10%
Source	DVI,RGB,CVBS,HDMI,YUV,SDI etc
Operating Temperature	-20°C~ +40°C
Storage Temperature	-20°C~ +60°C
Operating Humidity	10%~90%
Storage Humidity	10%~85%
Life Span	100,000 hrs

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to LED Cube System Sdn Bhd