










RK10S ROCK SERIES LED DISPLAY

RK10S



Features

RK10S P10 Outdoor Full Color LED Display

-  Cabinet only weighs 17kg, thickness 75mm, saving transportation cost and labor intensity;
-  Spring locks connect the cabinets vertically, hanging max 15 cabinets in a line;
-  Macromolecular flexible mask with glareless surface and better contrast ratio;
-  Fast spring locks connect the cabinets horizontally, only 10 seconds for per cabinet;
-  Nanotechnology and unique positioning system, making the installation and dismantlement in one step;
-  All external cable with quick inserted plug for easy installation and maintenance;
-  Signal and power indicator & reset button well shows the working condition of the whole screen;
-  Adopting Silica gel to make the cabinet waterproof and sealed, IP65

Specification

Item	Value
Pixel Pitch(mm)	10mm
Pixel Density(pixels / m ²)	35156dots/m2
LED Configuration	1R,1G,1B
Colors	>16.7M
Brightness(nits)	4500CD/M2
Grey Level(bit)	14bit
Refresh Rate(Hz)	>960HZ
Viewing Angle(Deg.)	H: 140/ V:140
Dimension	640mm x 640mm
Resolution(pixels)	640mm x 640mm
Panel Weight(kg)	17KG
Protection Level	IP65
Input Voltage	AC 110V~220V+/-10%
Source	DVI,RGB,CVBS,HDMI,YUV,SDI etc
Operating Temperature	-20°C~ +40°C
Storage Temperature	-20°C~ +60°C
Operating Humidity	10%~90%
Storage Humidity	10%~85%
Life Span	100,000 hrs
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to LED Cube System Sdn Bhd	