

R3II

BRING EVERYTHING CLOSER TO YOU



Seamless Design

Every Panel is Manufactured with CNC auto-machines of high precision. So that to guarantee its seamless during assembly




Slimmer & Lighter Stage Rental LED Display

- Pixel pitch: 3.9 mm
- Pixel configuration: SMD
- Brightness: 1200 nits
- Refresh rate: 1920 Hz
- Drive mode: 1/16 scan
- Panel dimension: 500 × 500 × 90mm

Light & Slim Panel

Each Panel is carefully crafted and Light weight.




Magnet Design(optional)

Push the module from the back.

Special Structure

Take it out directly from the front or back.




R311

Features Application Specs Order

ITEM	VALUE
Pixel Pitch(mm)	3.9
Pixel Density(pixels/m ²)	65746
Viewing Angle(Deg.)	140(H)/140(V)
Brightness(nits)	1200
Grey Level(bit)	16
Refresh Rate(Hz)	1920
Panel Dimension(mm)	500(W) x 500(H) x 90(D)
Panel Dimension(inch)	19.69(W) x 19.69(H) x 3.54(D)
Panel Resolution(pixels)	128 x 128
Panel Weight(kg)	8
Hanging Panel Quantity(panels)	≤20(vertical)
Panel Type and Material	Die-casting aluminum
Module Size(mm)	250(W) x 250(H)
Module Size(inch)	9.84(W) x 9.84(H)
Protection Grade(Front/Rear)	IP40
Avg.Power Consumption(W/m ²)	240
Max.Power Consumption(W/m ²)	720
Drive Mode	1/16 scan
Brightness Adjustment	Manual/Auto/Programmable
Operating Temp/Humidity(°C/%RH)	-20~+40/10~90
Storage Temp/Humidity(°C/%RH)	-40~+60/10~80
Lifetime(hours)	≥50000(Nomal Temp)
Compliant Standard	CE,FCC,RoHS,TUV

Notes: Specifications are for reference only. Please contact our salesperson for details.
All rights are reserved to LED Cube System Sdn Bhd



LED CUBE SYSTEM SDN BHD (1049662-M)

63, Jalan Puteri 5/8, Bandar Puteri Puchong, 47000 Puchong Selangor, Malaysia
Tel.: +603-8068 4986 / 8052 4986 Fax.: +603-8068 4796 Email: klee.creator@yahoo.com